

# **INDUSTRIAL** **SEAL** **PRO™**

*is the solution!*

## **DIRECTIONS:**

- \* **All filtration systems must be bypassed before installation of product.**
- \* **Do not overfill system.**

- 1. Remove container lid.**
- 2. Pour the contents of one bag into the bucket. (Note: Mix and apply one bag at a time to the system)**
- 3. Fill one inch from container top with water or coolant. (Note: Existing coolant can be used for mixing purposes)**
- 4. Attach provided mixing tool to battery/electric operated drill for best results. If battery/electric operated drill is not available, the material can be mixed with a mixing stick or paddle.**
- 5. Mix powder with mixing tool until powder is thoroughly mixed with the desired water or coolant.**
- 6. Inject the entire dosage into the system at a rate of approximately one gallon per minute. For best results install in suction line before pump. (Note: External pump can be used to install solution.)**

**NOTE: Do not install in expansion tank or chiller/compressor part of system. Residual powder may be left in bottom of the container that may require repeating the mixing steps.**

**Technical Hotline:**  
**Monday - Friday 8am-5pm EDT**  
 **855.974.2537**  
 **support@shalerpro.com**  
**www.rinksealpro.com**

**KEEP OUT OF REACH OF CHILDREN**

**Prolonged or frequent skin contact may cause  
allergic reaction in some individuals.**